



# PRIMER FOR THERMOPLASTIC ROAD MARKING

Automark Technologies (India) Pvt. Ltd. has specially designed primer for application of Thermoplastic Road marking material on concrete and old bitumen surface.

The Primer ensures excellent adhesion of the thermoplastic strips onto concrete or old bitumen, thereby increasing the life of road marking.

Being quick drying and easy to apply, no significant time under-runs are expected owing to primer application.

## **PROPERTIES OF AUTOMARK PRIMER FOR THERMOPLASTIC ROAD MARKING:**

<b>Sr. No.</b>	<b>Components</b>	<b>Results Required</b>	<b>Results Achieved</b>
1	Colour	Clear	Clear
2	Clarity	Translucent	Translucent
3	Viscosity at 300C as per Ford cup No.4	26 Sec.	26 Sec.
4	Weight per Ltr.	0.96 Kg./Ltr.	0.96 Kg./Ltr.
5	Volume Solids	33 + 2%	31
6	Drying Time at 300C	20 min.	11 min.



**automark Technologies (India) Pvt. Ltd.**

1<sup>st</sup> FLOOR, "SARAF COURT" OPPOSITE YASHWANT STADIUM, DHANTOLI, NAGPUR-440012, [MAHARASHTRA],  
 PHONE NO.: +91-712-6603-671 TO 678, +91-712-6615768, 2461111, FAX NO.: +91-712-6603-679 C.I.N.: U24290MH2002PTC135673  
 Email: [info@automarktech.com](mailto:info@automarktech.com); [www.automarktech.com](http://www.automarktech.com)  
 Plant: 18 km. Stone, Bothali Village, Wardha Road, Nagpur (M.S.) India

